



NEVILLE CHEMICAL COMPANY

Neville Island, Pittsburgh, Pennsylvania 15225
412-331-4200 FAX: 412-777-4234

MATERIAL SAFETY DATA

1. PRODUCT INFORMATION					
Date:	October 17, 2005	24 HOUR EMERGENCY ASSISTANCE Neville Chemical Company 412-331-4200 CHEMTREC 800-424-9300			
Tradename:	NEVOXY® EPX-LH Resin				
D.O.T. Shipping Name:	Synthetic Resin Non Hazardous Resin, Coal Tar or Petroleum Class 55 (in non-bulk packaging)	HMIS Hazard Rating			
Chemical Name and Synonyms:		Least	0	Health	1
Chemical Family:	Alkylated Phenol	Slight	1	Flammable	1
CAS No:		Moderate	2	Reactivity	0
WHMIS:	EPA Accession Number 123581	High	3		
		Extreme	4	Personal Protection	X
	Not Regulated	Neville Recommends B Minimum			

2. HAZARDOUS INGREDIENTS	
Principal Hazardous Components (Chemical and Common Names)	
None	

3. PHYSICAL DATA			
Softening Point, R&B°C	NA	Percent Volatiles (by Weight)	Approx. 1.5
Specific Gravity	Approx. 1.03 @ 25°C	Evaporation Rate (Water =1)	<1
Boiling Point (°F) Initial	NA		
Solubility in Water	Negligible	Vapor Pressure (mm Hg.)	NDA
Appearance and Odor	Clear Liquid, Slight Phenolic Odor	Vapor Density (Air = 1)	NDA

4. FIRE AND EXPLOSION HAZARD DATA						
Flash Point:	330°F (COC)	Flammable Limits	LEL	NDA	UEL	NDA
Extinguishing Media:	Water Spray, Dry Chemical, CO ₂ , Foam	Autoignition Temperature	NDA			
Special Fire Fighting Procedures:	Do not enter confined fire space without proper protective equipment, including a NIOSH approved SCBA. Use water spray to cool fire-exposed surfaces and to protect personnel.					
Unusual Fire and Explosion Hazards:	None					

5. HEALTH HAZARD DATA	
Threshold Limit Value:	NE, Recommend 5 mg/m ³ for mineral oil mist if used under misting conditions.
Signs and Symptoms of Exposure	
Acute Overexposure:	Not likely to cause any significant acute toxicological effects.
Chronic Overexposure:	No chronic effects known.
Medical Conditions Generally Aggravated by Exposure:	May cause skin, eye and mucous membrane irritation.
Primary Routes of Entry:	Inhalation of oil mist if product is aerosoled.
Eye Irritation:	May cause irritation
Skin Irritation:	May cause skin irritation.

(Continued on Reverse Side)

NA = Not Applicable
NE = None Established
NDA = No Data Available

5. HEALTH HAZARD DATA (Continued)

This mixture is not listed as a carcinogen or potential carcinogen by NTP, IARC or OSHA.	
OSHA Permissible Exposure Limit:	NE, Recommend 5 mg/m ³ for mineral oil mist.
ACGIH Threshold Limit Value:	NE, Recommend 5 mg/m ³ for mineral oil mist, ceiling 10 mg/m ³
Emergency and First Aid Procedures	
Inhalation:	Remove victim to fresh air and provide oxygen if breathing is difficult.
Eyes:	Flush eyes with copious quantities of water while holding eyelids open. If irritation persists, consult physician.
Skin:	Wash skin with soapy water. Use emollient skin creams. If irritation persists call a physician.
Ingestion:	Do not induce vomiting. Get medical attention.

6. REACTIVITY DATA

Stability:	This product is stable under normal conditions and hazardous polymerization will not occur.		
Conditions to Avoid:	Open flames, high temperatures, electric arc.		
Incompatibility (Materials to Avoid):	Oxidizers	Hazardous Decomposition Products	CO CO ₂

7. SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled:	At elevated temperatures, vapors can spread and result in flash fire. Eliminate sources of ignition. Recover and reclaim large quantities. Collect small amounts with suitable absorbent and place in sealable containers. Keep out of sewers and other public water systems.
Waste Disposal:	Reclaim or dispose of in accordance with local, state and federal regulations.

8. SPECIAL PROTECTION INFORMATION

Respiratory Protection:	NIOSH approved organic vapor respirator in accordance with 29 CFR 1910.134 if recommended PEL is exceeded.
Ventilation:	Provide explosion proof ventilation as required to control vapor levels.
Protective Gloves:	Rubber, neoprene if splashing is a problem.
Eye Protection:	Safety glasses and a face shield if splashing is a problem.
Other Equipment:	Wear other protective equipment as required to minimize skin contact.

9. SPECIAL PRECAUTIONS

Precautions to be taken in handling:	Eliminate ignition sources, use explosion proof equipment. Conveying and processing equipment should be spark-proof, electrically bonded and grounded.
Other Precautions:	Wash with soap and water before eating, drinking, smoking or using toilet facilities. Launder contaminated clothing before reuse.

10. OTHER REGULATORY INFORMATION

All components of this mixture are on the TSCA Inventory.
This material is not on the Canadian DSL.
This material is not regulated under SARA Title III, Section 302 and does not contain any substance above the de minimus level for Section 313.