

MATERIAL SAFETY DATA SHEET

SECTION I - PRODUCT IDENTIFICATION

SELLER:/DISTRIBUTOR

Technick Products, Inc
665 Martin Street
Rahway, NJ 07065

PHONE: (732)388-7755
FACSIMILE: (732)499-8222

MANUFACTURER: FINE ORGANICS- INDIA(ISO 9001 Certified)

Chemical name & synonyms: Process aids

Trade name: **Rubaid 222**

SECTION II - INGREDIENTS

<u>MATERIAL</u>	<u>CAS#</u>	<u>%</u>	<u>EXPOSURE CRITERIA</u>
<u>Mixture fatty acid derivatives*</u>			

This product does not contain any hazardous chemicals as defined by the OSHA hazard Communication standard/ (29 CFR 1910.1200/)

** All ingredients are listed under TSCA(USA) , EINECS(Europe), DSL (Canada)*

SECTION III - PHYSICAL DATA

Boiling Point: 760 mm Hg	N / D
Melting point: (ASTM D-127)	55-65
Specific Gravity:(H ₂ O = 1)	0.95
Vapor Pressure:	N/D
Vapor density (Air=1)	N/D
Solubility in H ₂ O:(% by WT.)	Insoluble
% volatiles by volume:	<1% @105 C
Evaporation rate. _____ =1	N/D
Appearance and Odor:	Creamish powder

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash point (and method used):	290 C° (COC)
Flammable limits in air:(% by volume)	N / A
Extinguishing media:	Water fog, Foam, CO ₂ , Dry chemical .
Special fire fighting procedures:	Do not use heavy stream of water.
Unusual fire and explosion hazard:	None

MATERIAL SAFETY DATA SHEET

RUBAID -222

<u>SECTION V - REACTIVITY DATA</u>	
Stability (Normal Conditions):	Stable
Incompatibility (Materials to avoid):	Strong oxidizing agents. (Bromine, chromic acid etc.)
Hazardous decomposition products:	Carbon Monoxide, CO ₂ from burning.
Hazardous polymerization:	Will not occur.
<u>SECTION VI - HEALTH HAZARD INFORMATION</u>	
Exposure limit:	N / D
Effects of overexposure inhalation:	Remove to fresh air.
Ingestion:	Contact a physician immediately.
Skin or eye contact:	Skin: no effect known. Eye: mild irritant.
<i>Emergency and first aid procedures</i>	
Inhalation:	Expose to fresh air.
Ingestion:	Induce vomiting, consult physician.
Skin:	Wash with mild soap & water.
Eyes:	Flush liberally with water for 15 Min.
<u>SECTION VII - SPECIAL PROTECTION INFORMATION</u>	
Ventilation requirements:	Standard local or mechanical to avoid dust.
Respiratory protection (Specify type):	Use NIOSH/OSHA approved dust mask.
Eye protection:	Safety glasses.
Gloves (Specify type):	Plastic or rubber.
Other protective equipment:	Protective apron.
<u>SECTION VIII - SPILL OR LEAK PROCEDURES</u>	
If material is released or spilled:	Ordinary procedure are adequate. Melted material can cause thermal burns. Can be burned or landfilled.
Waste disposal method:	Dispose off in accordance with all applicable federal, state and local regulations.

MATERIAL SAFETY DATA SHEET

RUBAID 222

HMIS RATINGS: Health: 1 Flammability: 1 Reactivity: 0
NFPA RATINGS: Health: 1 Flammability: 1 Reactivity: 0 Other: none

SECTION IX - SPECIAL PRECAUTIONS

Precautions to be taken in	Keep container closed until ready for use. Avoid long term storage in extreme temperatures.
Other precautions:	Maximum storage temperature 120° F.
Shipping name:	<u>DOT Plastic raw material - Unrestricted</u> IATA

PREPARED BY: Mr. Nick Mehta

Revision date: March 10, 2007

Supersedes: All previous

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of damage, or expense, direct or consequential arising out of their use.

