

Technical Data Sheet

NORDEL 4725P PRIME

Technical Name: Nordel 4725P Prime

CAS #: See Below

Appearance: Pellets Translucent

Technical Parameters: Min Max

		IIIAA
Mooney Viscosity ML1+4 @125 deg C	21	29
Ethylene WT	68%	72%
ENB WT	4.5%	5.3%
Volatiles, Total WT		0.4
Gel conc (200) <than 12="" 5.0="" count,="" m2<="" per="" td=""><td>Pass</td><td></td></than>	Pass	
Yellowness Index		7

Ethylene-propylene-ethylidenenoborneneterpolymer CAS # 25038-36-2 >99.0-<=100.0 %

5-Ethylidenebicyclo (2.2.1)hept-2-ene CAS# 16219-75-3 >0.005-<=0.016%

The above information has been compiled from what we believe to be credible sources. To our knowledge the information is accurate and reliable, however, it is not guaranteed. Any recommendations issued by HB Chemical personnel or literature is derived from experience and by no means should be taken as fact or construed as a recommendation to violate of any law, regulation or patent. It is the users responsibility to determine the suitability of any HB supplied material in their application. The individual conditions of each customer are well outside of our control and we cannot be held liable for its functionality and use. Please contact our office should you need specific information beyond what is supplied above. As with all Chemical usage safety precautions beyond the stated are highly recommended.

1665 ENTERPRISE PARKWAY, TWINSBURG, OH, 44087 Tel: (330) 920-8023 Fax: (330) 920-0971